

壳管式干式蒸发器

Tube Dry-type Evaporator

Model	Heat exchange KW	外形尺寸 (mm)									进出尺寸				
		Contour dimension (mm)									Inlet and outlet dimension				
		A	B	L	D	E	h	Φ1	T	Φ	a	b	c	d	e
CB03	10.5	640	250	906	300	80	140	245	800	180	Φ22	Φ16	G1½	Rc1/2	Rc¼
CB05	17.6	640	250	906	300	80	140	245	800	180	Φ22	Φ16	G1½	Rc1/2	Rc¼
CB06	21.1	720	250	986	300	80	140	245	880	180	Φ28	Φ16	G1½	Rc1/2	Rc¼
CB08	28.2	820	350	1086	400	100	160	285	980	219	Φ28	Φ16	G1½	Rc1/2	Rc¼
CB10	35.2	940	350	1206	400	100	160	285	1100	219	Φ35	Φ16	G2	Rc1/2	Rc¼
CB12	42.2	1140	350	1406	400	100	160	285	1300	219	Φ42	Φ22	G2	Rc1/2	Rc¼
CB15	52.8	1140	350	1406	400	100	160	285	1300	219	Φ42	Φ22	G2	Rc1/2	Rc¼
CB20	70	1340	350	1606	400	100	160	285	1500	219	Φ54	Φ28	G2½	Rc1/2	Rc¼
CB25	88	1440	350	1706	400	100	160	285	1600	219	Φ54	Φ28	G2½	Rc1/2	Rc¼
CB30	105	1440	350	1716	400	100	200	350	1600	273	Φ54	Φ35	G3	Rc1/2	Rc¼
CB35	123	1600	350	1916	400	100	200	350	1800	273	Φ68	Φ35	G3	Rc1/2	Rc¼
CB40	140	1600	350	1916	400	100	200	350	1800	273	Φ68	Φ35	G3	Rc1/2	Rc¼
CB45	158	1600	400	1916	450	100	240	400	1800	325	Φ68	Φ35	G3	Rc1/2	Rc¼
CB50	176	1600	400	1916	450	100	240	400	1800	325	Φ68	Φ35	G3	Rc1/2	Rc¼
CB60	211	1800	400	2116	450	120	240	400	2000	325	Φ68	Φ35	G4	Rc1/2	Rc¼
CB70	246	2100	400	2416	450	120	240	400	2300	325	Φ68	Φ42	G4	Rc1/2	Rc¼
CB80	281	2100	400	2416	450	120	270	460	2300	377	Φ68	Φ42	G4	Rc1/2	Rc¼
CB90	316	2100	400	2416	450	120	270	460	2300	377	Φ68	Φ42	G4	Rc1/2	Rc¼
CB100	352	2100	400	2416	450	120	270	460	2300	377	Φ68	Φ42	G4	Rc1/2	Rc¼
CB110	387	2100	400	2416	450	120	270	460	2300	377	Φ68	Φ42	G4	Rc1/2	Rc¼
CB120	422	2300	400	2616	450	120	270	460	2500	377	Φ68	Φ42	G4	Rc1/2	Rc¼

Design Parameter: Influent temperature(t1) is 12°C, drainage temperature(t2) is 7°C, sunction overheating temperature Dts=4°C., evaporation temperature te=2°C

